3D Reflective

UNITRADE

Update July 2025, Rev.1

Product Information

- Enhance your designs with a unique 3D reflective effect.
- Reflective Luminance (cd/lux/m^2): Silver ≥500; Dark Gray ≥230; Rainbow ≥130

Application to

- Cotton, polyester, and poly-cotton blends

Technical Data

Material Composition	PU	**Carrier**	Adhesive
Thickness (㎛)	600 ㎛	**Roll Size**	50 cm × 25 m
Wash Fastness	30 washes	**Washing Temperature**	Up to 45°C

Application Instructions

Suggested Cutting Settings			
Cutting Machine	Blade	Pressure	Speed
Graphtec CE6000-60	45°	24-26	30cm/sec

- A test cut is highly recommended to prevent errors and ensure clean results.

Transfer Settings			
Time	Temperature	Pressure	Peel
10sec	150-160°C	High	Cool

Storage & Care Instructions

- Wait 24 hours after application before the first wash.
- Machine wash cold using a mild detergent.
- Wash inside out.
- Do not use bleach or strong chemical agents.
- Do not dry clean.
- Iron on the reverse side only.
- Store at 18°C to 26°C. Shelf life: up to 2 years under proper storage conditions.
- Keep away from direct sunlight and dust.

Unitrade Co., Ltd.
#1004, Ace Gold Tower, 100, Gasan digital 1-ro, Geumcheon-gu, Seoul, Korea (08590)

WEBSITE : www.uni-trade.co.kr
E-MAIL: info@uni-trade.co.kr
YOUTUBE: @unitradekr
INSTAGRAM: @unitrade_korea